



Installation Instructions:

(Part # 17050101 RTG)

2007-2018 Jeep JK Heavy Duty Tire Carrier Kit

NOTE: Carefully read entire instructions thoroughly before attempting to install this part.

Parts Included	Qty	Parts Included	Qty
HD Tire Carrier	1	12mm-1.75.X 35-40mm Hex Head Bolt Gr. 8.8	4
Tire Mount Bracket Base	1	12mm- 1.75 Nylock Nut	4
Tire Mount Bracket	1	12mm Flat Washer	4
Tire Gate Mount	1	6mm-1.0 X 20mm Hex Head Bolt Gr. 8.8	4
Wheel Mount Stud: 1/2"-20	3	6mm- 1.0 Nylock Nut	4
Lug Nuts: 1/2"-20	3	6mm Flat Washer	8
Hardware Pack: Wheel Mount	1	8mm-1.25 X 40mm Hex Head Bolt Gr. 10.9	8
10mm-1.0 X 30mm Hex Head Bolt Gr. 8.8	5	8mm Flat Washer	8
10mm Nylock Nut	5	8mm Lock Washer	8
10mm Flat Washer	10	Third Brake Light Lower Bracket	1
		Third Brake Light Upper Bracket	1

INSTALLATION:

Step 1: Place the vehicle on a flat, level surface and engage the parking brake.

Step 2: Remove the spare tire and unbolt and remove the **OE** rear tire mount from the rear gate. Remove the **OE** third brake light assembly according to manufacturer's specifications.


Step 3: Carefully, remove the upper and lower **OE** plastic rear gate hinge covers. (Fig. A)



Installation Instructions:

(Part # 17050101 RTG)


2007-2018 Jeep JK Heavy Duty Tire Carrier Kit



Step 4: Using masking tape, secure the rear gate in place. Unbolt the (10) OE bolts securing the upper and lower OE hinges to the rear gate. Save the OE hardware for reinstallation.

(Fig. B)

NOTE: Place a block of wood between the bumper and the tailgate, placing slight pressure on both. This will prevent tailgate misalignment when OE hardware is removed.





Installation Instructions:

(Part # 17050101 RTG)

2007-2018 Jeep JK Heavy Duty Tire Carrier Kit

Step 5: Lift the HD tire carrier into place and secure to **OE** hinge points using the previously removed **(4) OE** bolts. Tighten the **(4) OE** hinge bolts. Make sure all remaining HD tire carrier mounting holes line up with existing holes in the rear gate before tightening the **OE** bolts. (Fig. C)

NOTE: *If the tailgate moved, realign as necessary. Starting a few bolts in the remaining mounting holes will help to ensure the mounting holes are properly aligned.*

Step 6: Torque the **OE** hinge bolts, starting with the outside bolts first, according to manufacturers specifications. Carefully, open the rear gate and torque the inner hinge bolts according to manufacturer's.



NOTE: *It is recommended to apply medium strength (blue) threadlocker to the OE hinge bolts.*



Installation Instructions:

(Part # 17050101 RTG)

2007-2018 Jeep JK Heavy Duty Tire Carrier Kit






Installation Instructions:

(Part # 17050101 RTG)

2007-2018 Jeep JK Heavy Duty Tire Carrier Kit

Step 7: Press the wheel mount studs, in your desired pattern, into the tire mount bracket base .
(Fig. E)

NOTE: *The studs may be pressed into place. DO NOT use lug nuts to install the studs.*



Step 8: Assemble the wheel mount bracket (**tire mount bracket & tire mount bracket base**) using the supplied (5) 10mm X 30mm bolts and hardware. Leave the bolts loose at this time. Lay the spare tire face down on the ground and install the wheel mount bracket temporarily onto the spare tire. **(Fig. F)**

Step 9: With the spare tire face down, lay a ruler or a flat bar across the tire and adjust the wheel mount bracket assembly until the base makes contact with the ruler or flat bar. Torque the wheel mount bracket assembly bolts to ?? ft./lbs. **(Fig. F)**


NOTE: *The assembled bracket may not line up perfectly with the straight edge.*



Installation Instructions:

(Part # 17050101 RTG)

2007-2018 Jeep JK Heavy Duty Tire Carrier Kit



Step 10: Secure the tire mount bracket assembly (**outside**) and the 3rd brake light lower bracket (**inside**) to the tire carrier mount using the (4) supplied 12mmX 35mm bolts and hardware. Torque 12mm hardware to 80 ft./lbs. (Fig. G)

NOTE: The size of the spare tire will determine the mounting height of the bracket. If possible, it is better to have the tire fit tighter against the straight edge/tire gate to avoid excess vibration.


TIP: For off-road applications, raise the tire position for more departure angle. For street driven applications, lower the tire position for greater rear window vision.




Installation Instructions:

(Part # 17050101 RTG)

2007-2018 Jeep JK Heavy Duty Tire Carrier Kit



Step 11: Secure the tire carrier mount assembly to the rear gate mounting holes and HD tire carrier using the (8) supplied **8mm X 40mm** bolts and washers. Torque the **8mm** hardware to factory ft./lbs. (Fig. H)



Step 12: Install the spare tire to the tire mount bracket and secure using the supplied lug nuts.




Installation Instructions:

(Part # 17050101 RTG)

2007-2018 Jeep JK Heavy Duty Tire Carrier Kit

Step 13: If a third brake light is being used, install the third brake light upper bracket onto the third brake light lower bracket and secure using the (4) supplied 6mm X 20mm bolts and hardware. (Fig. I)

IMPORTANT!: *Be sure third brake light is mounted so it will be visible above the spare tire.*



Step 14: Remove the (2) OE screws from the OE plastic third brake light assembly. Install the OE front plastic panel and lens into the new third brake light assembly using the (2) previously removed OE screws. (Fig. I)

Step 15: Depending on the mounting position of the third brake light assembly the wiring harness may need to be extended. Extend the third brake light wiring harness to the passenger side hinge, then up the tire gate. This can simply be done by splicing the wire and using some insulated butt splice connectors and 18 gauge wire, extend the wire to the appropriate length. It is recommended to have this done by an experienced electrical installer.

IMPORTANT!: *Make sure there is enough slack in the wire throughout the tailgate travel.*



Installation Instructions:

(Part # 17050101 RTG)

2007-2018 Jeep JK Heavy Duty Tire Carrier Kit

Step 16: Adjust the HD tire gate assembly for level and re-torque mounting hardware as necessary.

Step 17: Installation is now complete. (Fig. J)

Step 18: Periodically check and re-torque mounting hardware. Especially after off-road use.



Product cleaning and maintenance instructions



Installation Instructions:

(Part # 17050101 RTG)

2007-2018 Jeep JK Heavy Duty Tire Carrier Kit

Stainless Steel Finish – Aluminum polish may be used to polish small scratches and scuffs on the finish. Mild soap, window or glass cleaner may be used to clean the finish. **Dual state powder coat finish** – Mild soap, window or glass cleaner may be used to clean the finish. In order to protect the finish, you may wax your product on a regular basis with pure carnauba automotive wax. Do not use any types of soap, polish or was that contains abrasive that could damage the finish. **Textured coated finishes** should be cleaned with a mild soap on a damp sponge. Do not apply polish or was that requires to be removed by means of buffing. This type of wax is commonly used at car wash facilities. **Chrome Finish** – Mild soap, window or glass cleaner may be used to clean the finish. In order to protect the finish you should wax your product on a regular basis with pure carnauba automotive wax. Do not use any types of soap, polish or was that contains abrasive that could damage the finish.

Limited Warranties

King 4WD's products are covered under the following limited warranties only. Note that the duration of the limited warranty differs according to the material and finish of the product purchased. Subject to the duration and conditions of the limited warranty stated below, King 4WD's warrants to the original retail purchaser that its products are free from defects in material and workmanship. All other warranties and representations express or implied, are hereby disclaimed, including fitness for merchantability and buyer's intended use or purpose. All parts are sold "AS IS" except for the limited warranties granted herein. Buyer assumes all risks as to the selection, suitability and performance of all goods and products selected. This limited warranty does not cover damage or impairment in any part due to misuse, improper installation, accident or contact with on-road or off-road hazards, product modification, improper or inadequate cleaning and/or maintenance. King 4WD's is not responsible for items damaged during shipping. This warranty is not transferable from the original buyer. For the original Buyer to be eligible for the limited warranty coverage, the Buyer must provide proof of purchase. King 4WD's strongly recommends returning the warranty registration card.

Customer's remedy hereunder shall be limited only to repair or replacement (at King 4WD's option) of any defective part(s) returned to King 4WD's at customer's expense. The determination of whether or not a returned part is defective or subject to coverage under the limited warranties stated herein shall be made at King 4WD's sole discretion.

To assure product quality, King 4WD's reserves the right to change product design, material, specification and finishes without prior notice to customers. This limited warranty gives you specific legal rights and you may also have other rights, which may vary from state to state. Some states do not allow limitations on how long an implied warranty lasts, so the above



Installation Instructions:

(Part # 17050101 RTG)

2007-2018 Jeep JK Heavy Duty Tire Carrier Kit

limitations may not apply as to you. Also, some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitations or exclusions may not apply to you. King 4WD's reserves the right to discontinue product lines and substitute products, or provide other remedies than those listed in this limited warranty for those discontinued products.

Warning

Rollover and other types of vehicle accidents may result in serious injury or death to you, your passengers and others sharing the road. King 4WD's accessories are decorative and are not intended to reduce or avoid injury or damage in the event of an accident. The weight and location of King 4WD's accessories may affect your vehicles' handling, stability and performance, creating an increased risk of accident or rollover. Before installing any accessory, check state laws and assure that the accessory will not obscure any lights or interfere with proper operation on your vehicle's safety equipment. Consult your owner's manual and the King 4WD's instructions, or additional safety information. King 4WD's products, nor the warnings contained herein, are not a substitute for your safe driving. Don't drink and drive, always use seat belts and don't drive faster than conditions permit.
